

BETA TECH

Product Specification	Heavy Contract Carpet	Heavy Contract Carpet Tiles
Pile Yarn	100% SD Econyl Nylon	100% SD Econyl Nylon
Construction	Cut Pile	Cut Pile
Dyeing Method	Solution	Solution
Primary Backing	Non-Woven	Non-Woven
Secondary Backing	Action	Bitumen
Pile Weight	1100g/m ² ±	1100g/m ² ±
Total Weight	2000g/m ² ±	4500g/m ² ±
Pile Height	4.5mm nominal ±	4.5mm nominal ±
Total Thickness	6.5mm nominal ±	6.5mm nominal ±
Gauge	1/10th ±	1/10th ±
Standard Roll & Tile	30m x 4m Approx	50cm x 50cm

Technical Specification - Overall Performance Rating

Classification	Heavy Contract	Heavy Contract
Reaction to Fire	Cfl-s1	Bfl-s1
Thermal Resistance	0.07 M2KW	0.07 M2KW
Light Fastness	≥ 5	≥ 5
Wearability	≥ 4	≥ 4
Water Fastness	≥ 4	≥ 4
Noise Impact Test	24dB	25dB

Installation

Suitability

Beta Tech is ideally suited for a variety of applications such as hotels, offices, banks, schools, libraries, universities and colleges, and many other institutional and commercial installations.

Installation

Before installation, check for quality, texture, finish, colour match and that all carpet to be used in the same area is from the same dye batch. No claims will be considered after cutting and/or installation.

The tiles should be unpacked and allowed to acclimatise at a minimum 18°C for 48 hours. During winter (Oct-Mar) 72 hours minimum. Relative humidity should not be more than 75%.

All carpets should be fitted in accordance with BS3525: 2001.

Recommended adhesives for Broadloom Carpet

For Permanent Bonding - Styccobond F3

Recommended adhesives for Carpet Tiles

For Permanent Bonding - Styccobond F3

SEAMS MUST BE SEALED WITH A SEAM SEALING ADHESIVE.

For Release Bonding - Styccobond F41.

Maintenance

Beta Tech should be vacuumed regularly and spillages attended to immediately. Regularly daily suction vacuum cleaning and occasional hot water extraction is recommended. Most stains can be removed by a good quality purpose made cleaner following the manufacturer's instructions.

10 Year Limited Wear Warranty. Contact the office for details.



Birch Carpets


318 Coleford Road, Sheffield, S9 5PH

Tel 0114 243 1230

Fax 0114 243 5118

Email info@birchcarpets.co.uk

Website www.birchcarpets.co.uk



Birch Carpets ± specification represents a nominal 10%

Birch Carpets reserves the right to change or modify specifications without giving prior notice