

BIRCH HEATHERS

Specification

Pile Yarn	100% PP
Construction	Cut Pile
Primary Backing	Woven
Secondary Backing	Duo
Pile Weight	1100g/m ² ± 5%
Total Weight	2070g/m ² ± 15%
Pile Height	9.5mm ± 2mm
Total Thickness	11.5mm ±
Gauge	1/8th
Stitch Rate	141, 750/m ² ± 10%
Width	4m & 5m
Classification	Heavy Domestic
Flammability EN 13501-1	Efl
Light Fastness 105-B02	≥ 5
Wearability 105-X12	≥ 4
Water Fastness 105-E01	≥ 4

Installation

All carpets should be fitted in accordance with BS5325: 2001.

Before installation, check for quality, texture, finish, colour match and that all carpet to be used in the same area is from the same dye batch. No claims will be considered after cutting and/or installation.

Maintenance

The carpet should be vacuum cleaned regularly and spillages attended to immediately. Regular daily suction vacuum cleaning and occasional hot water extraction is recommended. Most stains can be removed by a good quality purpose made chemical following the manufacturer's instructions. Do not use petrol or any similar product.

Due to the limitations of dye technology, colours may vary from those shown on the sampling. No claims will be considered as a result of improper application, installation or maintenance. Pile pressure marks, shading and soiling are not manufacturing defects.



Birch Carpets

318 Coleford Road, Sheffield, S9 5PH
Tel 0114 243 1230
Fax 0114 243 5118
Email info@birchcarpets.co.uk
Website www.birchcarpets.co.uk

