

Elegance

Feel THE DIFFERENCE

Feel the **luxury** under your feet

10mm


UHD+
Ultra High
Density Plus

Choosing the **right** underlay

Underlays are a great way to increase the **comfort** and **durability** of your flooring... but how do you choose one?

Broadly speaking, there are two key variables to consider when it comes to selecting underlays - **density** and **thickness**.

Floorwise have made the relationship between these two variables easy to understand with our unique **Bouncebackability** Index.



GOOD $\leftarrow$ $\rightarrow$ BEST



46dB

Impact sound reduction

TOG 2.54

Thermal insulation

Fantastic floors start with **floorwise**

Comfort ★★★★★☆☆ Durability ★★★★★★★★ Bouncebackability ★★★★★☆☆



Made in the
UK



Stitched crepe paper
acids extra stability



For the lifespan of all types
of carpet



This underlay uses
recycled material
and is completely
recyclable after use

wiseup@
www.floorwise.co.uk

Specification (typical values)

PHYSICAL PROPERTIES

Core material	Ultra high density recycled post industrial PU foam
Density (kg/m ³)	160
Top surface	Printed white stitched crepe paper
Bottom surface	Stabilising non-woven fleece bonded by clear film
Nominal thickness (mm)	10.00
Dimensions (m ²)	1.37m x 11.00m = 15.07
Roll weight (kg)	24.90

PRODUCT PERFORMANCE - BS EN 14499

RESULTS

STANDARD

Elongation at 30N - length / width (%)	<5.0 / <2.5	BS EN ISO 13934-1
Breaking strength - length / width (N)	> 195.0 / >70.0	
Loss in thickness after long term static loading (%)	<2.5	ISO 3416
Loss in thickness after dynamic loading (%)	<2.5	BS ISO 2094
Work of compression after dynamic loading (J/m ²)	> 190.0	BS 4098 / BS ISO 2094
Retained work of compression (%)	> 100.0	
Compression after dynamic loading (mm)	5.0	
Resistance to cracking	Pass	BS EN 14499
Assessment of wear	No negative effect	BS ISO 1036

OTHER RELEVANT DATA

Flammability

Hot metal nut test	Pass - Medium radius of effect	BS 5287
--------------------	--------------------------------	---------

Thermal Performance

Thermal resistance (tog)	2.54	BS 4745
--------------------------	------	---------

Acoustic Performance

Impact sound reduction (dB)	46	BS EN ISO 10140-3
-----------------------------	----	-------------------

USAGE CLASSIFICATION

L/U

Luxury Use


Floorwise reference: F9FTDEL/Issue 3/July 2023

Notes:

1. All values are nominal and may vary within our manufacturing tolerances
2. Some values may have been derived from the testing of similar products

10mm

Comfort ★★★★★☆☆ Durability ★★★★★★★ Bouncebackability ★★★★★☆☆