

Luxor

Product Specification	Velour	Rib
Pile Content	100% Polypropylene	100% Polypropylene
Construction	Fibre Bonded Carpet	Fibre Bonded Carpet
Backing	Rot Proof Gel	Rot Proof Gel
Pile Weight	900g/m ² ±	900g/m ² ±
Total Weight	1435g/m ² ±	1500g/m ² ±
Pile Height	3.0mm nominal ±	3.5mm nominal ±
Total Height	8.0mm nominal ±	7.5mm nominal ±
Width	4m	4m
Tile Size	30 Metres Approx	30 Metres Approx

Technical Specification	Technical Specification
Grading	Heavy Contract
Flammability	BS4790 Hot metal nut test: Low radius of ignition
Static Loading	Anti-Static
Abrasive Resistance	ISO 105 – X12 Wet or Dry 4 or above
Colour Fastness	Excellent colour fastness under ISO 105 – BO2 All colours 6 or

Suitability:

Luxor is ideally suited for a variety of applications such as offices, banks, universities, schools, care homes, libraries, computer rooms, changing / locker rooms and many other institutional, commercial and industrial installations.

Installation

Before installation, check for quality, texture, finish, colour match and that all carpet to be used in the same area is from the same dye batch. No claims will be considered after cutting and / or installation. All floors should be dry, clean and level. It is recommended that the carpet be fully adhered directly to the sub-floor using a proprietary adhesive (F556 all purpose flooring adhesive).

Maintenance:

To maintain the appearance of Luxor, it should be vacuumed regularly, and spillages should be removed as soon as possible using appropriate techniques and cleaning products. Occasional hot water extraction is recommended. Most stains can be removed by a good quality purpose made chemical following the manufacturers instruction. Do not use petrol or any similar product.

It is strongly recommended that a protecting mat, i.e.: Keyhole mat or similar, is used under castor chairs. Due to the limitations of dye technology, colours may vary from those shown on the sampling. No claims will be considered as a result of improper application, installation or maintenance. Pile pressure marks, shading and soiling are not manufacturing defects.

Birch Carpets ± specification represents nominal 10%.



Birch Carpets

Hazel Park Mills
318 Coleford Road,
Sheffield, S9 5PH
Tel 0114 243 1230
Email info@birchcarpets.co.uk

