

NOVA TECH

Product Specification	Heavy Contract Carpet	Heavy Contract Carpet Tiles
Pile Yarn	100% SD Nylon	100% SD Nylon
Construction	Loop Pile	Loop Pile
Dyeing Method	Solution	Solution
Primary Backing	Woven	Woven
Secondary Backing	Action	Bitumen
Pile Weight	500g/m ² ±	500g/m ² ±
Total Weight	1650g/m ² ±	3600g/m ² ±
Pile Height	3.0mm nominal ±	3.0mm nominal ±
Total Thickness	5.5mm nominal ±	6.0mm nominal ±
Gauge	1/10th ±	1/10th ±
Standard Roll & Tile Dimensions	30m x 4m Approx	50cm x 50cm

Technical Specification - Overall Performance Rating

Classification	Heavy Contract	Heavy Contract
Reaction to Fire	Cfl-s1 1658-CPR-3074	Bfl-s1 1658-CPR-3134
Thermal Resistance	0.07 M2KW	0.07 M2KW
Light Fastness	≥ 4	≥ 4
Rubbing Fastness	≥ 4	≥ 4
Water Resistance	≥ 4	≥ 4
Noise Impact Test	23dB	25dB
Sounds Absorption	0.15aw	0.15aw

Installation

Suitability

Nova Tech is ideally suited for a variety of applications such as offices, banks, schools, libraries, universities and colleges, and many other institutional, commercial installations.

Installation

Before installation, check for quality, texture, finish, colour match and that all carpet to be used in the same area is from the same dye batch. No claims will be considered after cutting and/or installation.

The tiles should be unpacked and allowed to acclimatise at a minimum 18°C for 48 hours. During winter (Oct-Mar) 72 hours minimum. Relative humidity should not be more than 75%.

All carpets should be fitted in accordance with BS3525: 2001.

Recommended adhesives for Broadloom Carpet

For Permanent Bonding - Styccobond F3

Recommended adhesives for Carpet Tiles

For Permanent Bonding - Styccobond F3

SEAMS MUST BE SEALED WITH A SEAM SEALING ADHESIVE.

For Release Bonding - Styccobond F41

Maintenance

Nova Tech should be vacuumed regularly and spillages attended to immediately. Regularly daily suction vacuum cleaning and occasional hot water extraction is recommended. Most stains can be removed by a good quality purpose made cleaner following the manufacturer's instructions.

10 Year Limited Wear Warranty. Contact the office for details.



Birch Carpets


318 Coleford Road, Sheffield, S9 5PH

Tel 0114 243 1230

Fax 0114 243 5118

Email info@birchcarpets.co.uk

Website www.birchcarpets.co.uk



Birch Carpets ± specification represents a nominal 10%

Birch Carpets reserves the right to change or modify specifications without giving prior notice