

PROFILE

Product Specification

Construction
Yarn Type
Machine
Tuft Density
Pile Height
Total Pile Thickness
Primary
Pile Weight
Total Weight
Backing Material
Box Content
Tile Size
Fire Classification
Static
Castor Chair
Contract Rating
Dimensional Stability

CARPET TILES

Tufted Loop Pile
100% Solution Dyed Nylon
1/10th gauge
176,000/m²
2.5mm ±
6mm ±
100gsm Non Woven Polyester
500g/m² ±
4050g/m² ±
Oxidised Bitumen with a spun bonded secondary
20 tiles - 5m²
50cm x 50cm
Cfl-s1 = B1 PASS
Below 200V, ie. below the level of human sensitivity
Exceeds Minimum Requirements
Heavy Contract
Passed Aachen DIN 54318

Installation

Wear warranty will apply where the tiles have been professionally fitted in accordance with BS 5325:2021. The tiles should be unpacked and allowed to acclimatise for a minimum of 48 hours at 18 °C before installation. During colder weather (Oct-Mar) this is extended to 72 hours minimum.

Recommended adhesives for carpet tiles

For permanent bonding: Styccobond F3
For release bonding: Styccobond F41

Maintenance


Profile® carpet tiles should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction Method' is recommended depending on conditions. Chair mats are recommended under castor chairs.

Application

Profile® is a heavy contract tufted loop pile carpet tile designed for offices, universities, schools and the health sector, where wearability and stain resistance is paramount.



BIRCH
CARPETS
MADE TO INSPIRE



The suppliers reserve the right to change or modify specifications without giving prior notice.
± specification represents nominal 10%.