

STYLE

Product Specification

Construction	
Yarn Type	
Machine	
Tuft Density	
Pile Height	
Total Pile Thickness	
Primary	
Pile Weight	
Total Weight	
Backing Material	
Box Content	
Tile Size	
Fire Classification	
Static Loading	
Sound Absorption (ISO 140-8)	
Wear Classification	
Dimensional Stability (EN986)	

CARPET TILES

Loop Pile
100% Solution Dyed Polypropylene
1/10th gauge
168,000/m ²
3mm ±
6mm ±
Non Woven
360g/m ² ±
3790g/m ² ±
Bitumen
20 tiles - 5m ²
50cm x 50cm
Cfl-s1:1658-CPR-3136
Anti-Static
21dB
Moderate Commercial Use
Pass

Installation

Wear warranty will apply where the tiles have been professionally fitted in accordance with BS 5325:2021. The tiles should be unpacked and allowed to acclimatise for a minimum of 48 hours at 18 °C before installation. During colder weather (Oct-Mar) this is extended to 72 hours minimum. For best visual results, it is recommended that tiles are laid checkerboard using directional arrows on the back.

Recommended adhesives for carpet tiles

For permanent bonding: Styccobond F3

For release bonding: Styccobond F41

Maintenance

Style® carpet tiles should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction Method' is recommended depending on conditions. Chair mats are recommended under Castor chairs.

Application

Style® is a commercial contract tufted loop pile carpet tile designed for use in moderate contract and heavy domestic conditions.

